

Mounting instruction: Skamol Glue Pistol



- 1** Cut a small hole at the top of the Skamol Glue bag.



- 2** Press the Skamol Glue bag to remove the air from the bag.



- 3** Take the Skamol Glue Pistol.



- 4** Remove the nozzle from the Skamol Glue Pistol.



- 5** Insert the Skamol Glue bag in the Skamol Glue Pistol. The small hole must point towards the opening.



- 6** Twist the Skamol Glue bag to fit it easily in the Skamol Glue Pistol.



- 7** Make sure the entire Skamol Glue bag is inside the Skamol Glue Pistol.



- 8** Attach the nozzle to the Skamol Glue Pistol.



- 9** The Skamol Glue Pistol is now ready for use.

- A** Remove dust from the surface of the SkamoEnclosure Board.
- B** Use Skamol Primer at the surfaces of the SkamoEnclosure Boards where the Skamol Glue will be applied.
- C** Add Skamol Glue on top of the SkamoEnclosure Board in a even layer.
- D** Push the SkamoEnclosure Boards in place. Remember Skamol Glue binds quickly.
- E** There is no curing time when the SkamoEnclosure Boards are glued, and you can insert the stove immediately.
- F** Remove the excess Skamol Glue liquid with a wet cloth. Remove the hardened Skamol Glue with a putty knife.

Skamol Group

Hasselager Centervej 1, 8260 Viby, Denmark

Tel.: +45 97 72 15 33

www.skamol.com